



LATEX GRAIN CRACK SEALER

Seals up stress cracks and checks in logs, timbers and wood siding.

- Ideal for log homes, timber frames and wood siding
- Easy to use – water clean up
- Expands and contracts 50%
- Bonds tight to wood
- Bridges gaps up to 1/2" wide
- Compatible with LIFELINE™ Natural Wood Finish and PERMA-CHINK™ Log Home Sealant

DIRECTIONS:

Crack or check must be clean, dry and free from dust, dirt, oils, solvents or silicones. Apply material into crack or check using loaded brush. Make short crossways strokes over cracks larger than 1/8". Brush length-ways with grain to smooth out material. Check Mate™ must have good contact with wood on sides of check or crack. Do not fill crack completely – seal just the outer areas.

Remove overflow immediately with damp cloth.
Be sure crack or check is completely sealed from end to end.
Clean up tools and work area with soap and water. Rinse well and allow to dry.
Store unused material in cool, dry place, tightly sealed.

DO NOT ALLOW TO FREEZE.

COVERAGE: 175-225 square feet per gallon.

CAUTIONS:

Do not take internally. If swallowed drink milk and consult physician immediately. Avoid prolonged contact with skin. Avoid direct contact with eyes. Wear eye protection while using. Keep out of reach of children. Use in well ventilated area.

MADE IN U.S.A



www.permachink.com