

# Product Information



The Log Home Care and Maintenance Authority

## Log Wash™ Log Home Cleaner

Periodically cleaning an exterior finish is an important step in maintaining the appearance and durability of a stained surface. The exterior surfaces of a log home are a settling ground for dust, pollen and other airborne contaminants that dull the surface and encourage mold growth. A light cleaning once or twice a year will keep a home looking beautiful and helps prolong the life of the exterior finish.

Log Wash is designed to remove dirt, grime, pollen and surface mold and mildew without harming the wood or the finish as long as the finish is in good condition. If during the washing process you notice areas where the stain or topcoat is coming off, it is probably time to apply a new coat of stain or topcoat. Request a copy of "Caring For Your Dream Home" for information about applying and maintaining LIFELINE stains and finishes.

### Features:

- Removes dirt, dust, and pollen from log surfaces.
- Will not harm finishes that are in good condition.
- Is safe to use on chinking and sealants.
- Is environmentally friendly.

### Application Tips:

1. Add one cup of Log Wash to one gallon of water.
2. Do not mix any other cleaners or bleach to the Log Wash solution.
3. Wet down the area to be cleaned with a water mist from your garden hose.
4. Apply wash solution to logs with a pump-up sprayer.
5. Clean small areas at a time.
6. Do not allow wash solution to dry on the logs.
7. Gently scrub with a soft bristled brush.
8. Clean from the bottom up, rinse from the top down.

Log Wash is formulated as maintenance cleaner, not as a cleaner to prepare the wood for a new coat of stain or topcoat.

### Application:

Add one (1) cup of Log Wash to one (1) gallon of water and mix or stir. Warm water (not hot) works better than cold water. **DO NOT ADD MORE THAN ONE CUP PER GALLON. A more concentrated solution may harm the finish.**

Plan on cleaning small areas at a time since Log Wash needs to stay wet in order to do its job. Start by wetting down the wall with mist from your garden hose.

Apply the Log Wash solution starting at the bottom of the wall and work your way up. Work only an area big enough so that the Log Wash is on the wall for about 5 to 10 minutes. Gently scrub the wall with a soft bristled brush then, using a mist setting on the hose nozzle, thoroughly rinse the Log Wash from the top down.

**Remember, wash from the bottom up, rinse from the top down.** This will help prevent streaks and drip marks.

### Storage:

Store Log Wash out of direct sunlight and protect from freezing. Although Log Wash is freeze-thaw stable, if the product is accidentally frozen, allow to thaw and check for suitability of use before applying.

### Coverage:

One gallon of Log Wash concentrate makes approximately 16 gallons of cleaning solution that will clean about 2400 to 3400 square feet of wood surface area. Each gallon of Log Wash solution will clean approximately 150 to 200 square feet of wood surface.

### Packaging:

Log Wash is available in one-gallon containers.

### Shelf Life:

One year from date of purchase.

### Company Stores

Washington/Western Division

1-800-548-1231

Tennessee/Eastern Division

1-800-548-3554

Sevierville, TN

1-888-441-1116

Minnesota Branch

1-877-244-6548

Colorado Branch

1-800-433-8781

Montana Branch

1-800-479-7090

### Stocking Distributors

Canadian Log Home Supply, Canada

1-800-746-7773

Hess Log Home Supplies, PA

1-800-257-4864

Log Home Center & Supply, IN

1-800-773-6223

Steels Industrial Products, Ltd., B.C.

1-877-846-7502

Timeless Wood Care Products, MI

1-800-564-2987

visit us  
online  
[www.permachink.com](http://www.permachink.com)