

Cetol® BL Interior Clear

A quick drying, low odor, waterborne, transparent finish for interior wood surfaces which enhances the natural beauty of the wood grain while providing a hard wearing and scratch resistant surface. Cetol BL Interior Clear can be used on its own or as a topcoat for Cetol Interior Stain. 3 sheen levels are available: Low Lustre, Satin and Gloss.

Transparent finish ensures maximum visibility of wood grain.

Unique coating which seals and protects.

Scratch resistant.

Quick drying - low odor.

Excellent flow.

Easy to clean.

Waterborne.

Choice of 3 sheen levels.

Used as a transparent protective finish for all interior wood applications except for floors, table tops and kitchen counters. May be used to topcoat Cetol Interior Stain. (Refer to the Sikkens Product Application Guide for details.)

Method - Good quality long-haired, nylon polyester brush or spray.

Temperature - 50°F - 95°F (10°C - 35°C).

Thinning - None; ready to use after stirring well.

Cleaning of Equipment - Clean promptly with soap and clean water.

Coverage - Approximately 400-500 sq. ft. per U.S. gallon (10-12 sq. m. per liter) per coat.

Drying Time - Touch dry after 1-2 hours; recoatable after 4 hours.

CHARACTERISTICS

USE

APPLICATION

Viscosity - 2.8 - 3.4 Poise at 73°F (23°C)

Density - 1.02 - 1.03 kg/dm³

Solids by Weight - 28 ± 1%

Solids by Volume - 25 ± 1%

Sheen Levels - Low Lustre, Satin, Gloss

Flow - Very Good

Adhesion - Good

Water Resistance - Moderate

Alcohol Resistance - Low

V.O.C. - 2.42 lbs./gal., 289 g/L - water free

Colorless - 003

U.S. quart, U.S. gallon, U.S. 5 gallon

Shelf Life - Approximately 3 years in an unopened container.

Storage - Protect from frost. Keep from freezing.

FLASHPOINT:

> 212°F (100°C)

WARNINGS:

Do not take internally.

Keep out of reach of children.

Close container after use.

FIRST AID TREATMENT:

Refer to the Material Safety Data Sheet.

The technical information and suggestions for use made herein are based on Akzo Nobel Coatings Inc.'s research and experience and are believed to be reliable, but such information and suggestions do not constitute a warranty.

Since Akzo Nobel Coatings has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise, the suitability of the product for their purposes. When testing, the complete system that has been chosen must be applied.

PROPERTIES

COLOR RANGE

PACKAGING

STORAGE

HEALTH & SAFETY DATA

PRODUCT DISCLAIMER