

## Cetol® SRD

Cetol SRD is a translucent exterior wood finish based on a special oil and alkyd resin combination. The product uses a transparent iron-oxide pigmentation to provide an ultraviolet screen for the wood.

Highly transparent; ensures optimum visibility of the grain.

Highly microporous for wet areas.

Non-film building.

Single coat application.

Contains fungicide to provide protection against surface mold growth.

Protects wood from ultraviolet-light.

Easy application.

Cetol SRD is for application to areas normally troublesome to coat with film-forming products. These application areas include roofs, wall shakes, shingles, and decks. One coat applications (refer to Sikkens Application Guide for details).

**Method** - Garden pump sprayer, long-haired natural bristle brush, HVLP, airless sprayer or roller. All methods must be back brushed using a good quality long hair natural brush. In the case of shakes & shingles, dipping is recommended, then brushing any excess drops until smooth.

**Temperature** - 10° C - 35° C (50° F - 95° F).

**Thinning** - None; ready to use after stirring thoroughly.

**Cleaning of Equipment** - Clean promptly with mineral spirits or Varsol.

**Coverage** - Approximately 5-7 sq. m. per liter (200-300 sq. ft. per U.S. gallon) per coat on smooth wood. Approximately 2.5-3.75 sq. m. per liter (100-150 sq. ft. per U.S. gallon) per coat on rough wood.

**Drying Time** - Touch dry after 2 hours, recoatable, at 20° C (68° F) and 65% relative humidity. During application, moisture content of the wood substrate should not exceed 21%.

## CHARACTERISTICS

## USE

## APPLICATION

**Viscosity** - 16 to 17 Pa. s20° C (68° F).

**Density** - 0.88 kg/dm<sup>3</sup> ± .06

**Solids by Weight** - 41 to 43%

**Solids by Volume** - 36 to 39%

**Gloss Level** - Satin Finish

**Flow** - Excellent

**Durability** - Apply a maintenance coat when visually necessary.

**V.O.C.** - Less than 4.59 lbs./gal., 550 g/L - water free

(005) Natural Oak  
(072) Butternut  
(085) Teak  
(089) Redwood  
(113) Cape Cod Grey  
(996) Natural Light

U.S. Gallon, U.S. 5 Gallon

**Shelf Life** - Approximately 5 years in an unopened container.

#### FLASHPOINT:

Cetol SRD 105° F (40° C) SCC

#### WARNINGS:

DANGER! RAGS, STEEL WOOL, BRUSHES, ROLLERS AND ANY WASTE WET, SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISPOSED OR STORED. To avoid a spontaneous combustion fire, immediately after each use place rags, steel wool, brushes, rollers or waste in a sealed, water filled metal container. Keep away from combustible materials. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency. Do not take internally. Keep out of reach of children.

#### FIRST AID TREATMENT:

Refer to the Material Safety Data Sheet

The technical information and suggestions for use made herein are based on Akzo Nobel Coatings Inc.'s research and experience and are believed to be reliable, but such information and suggestions do not constitute a warranty.

Since Akzo Nobel Coatings Inc. has no control over the conditions under which the product is transported, stored, handled, used or applied. Buyers must determine for themselves, by preliminary tests or otherwise, the suitability of the product for their purposes. When testing, the complete system that has been chosen must be applied.

## PROPERTIES

## COLOR RANGE

## PACKAGING

## STORAGE

## HEALTH & SAFETY DATA

## PRODUCT DISCLAIMER