

Rubbol® DEK

A durable solid color exterior wood coating formulated specifically for decks. Rubbol DEK is based on a blend of alkyd resins, oils, and high-quality pigments.

Solid, vivid, and lightfast colors.

Penetrates and protects exterior wood decks against the elements.

Microporous.

Easy application.

Complete coverage and hiding.

Minimal maintenance.

Used as a protective coating for wood decks. (Refer to the Sikkens Product Application Guide for details.)

Method - Long-haired nylon polyester brush.

Temperature - 50° F - 95° F (10° C - 35° C)

Thinning - Not recommended.

Cleaning of Equipment - Mineral spirits or varsol.

Coverage (approximate) -

Smooth Wood: use 350-450 sq. ft. per U.S. gallon (one liter per 8.5-11 sq. m.) per coat.

Textured Wood: varies with surface porosity and roughness. Approximately half the coverage of smooth wood.

Drying Time - Touch dry after 3-4 hours and recoatable after 24 hours at 20° C (68° F) and 65% relative humidity.

During application the moisture content of the wood should not exceed 18%.

CHARACTERISTICS

USE

APPLICATION

GENERAL REMARKS

Viscosity - R.M.: 5.8 - 8.5 Poise Tint Bases: 4.8 - 6.0 Poise
Density - R.M.: 1.01.08 kg/dm³ Tint Bases: 1.15 - 1.17
Solids by Weight - R.M.: 33-37% Tint Bases: 58 - 62%
Solids by Volume - R.M.: 25-28% Tint Bases: 44 - 48%
Gloss Level - Satin Finish
Flow - Good
V.O.C. - 340-350 g/L - Less than 2.9 lbs./gal., 350 g/L - water free

Tint Bases: (110) Light Base
(120) Medium Base
(130) Deep Base

Ready Mix (R.M.):

(052) Navajo Red
(058) Oxford Brown
(100) White
(201) Chestnut Brown
(414) Forest Green

U.S. quart (only available in specific colors)
U.S. gallon (tint bases available in gallons only)

Shelf Life - Approximately 3 years in an unopened container.

Storage - Keep from freezing.

FLASHPOINT:

Approx. 106° F (41° C) (ASTM)

WARNINGS:

DANGER! RAGS, STEEL WOOL, BRUSHES, ROLLERS AND ANY WASTE WET, SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISPOSED OR STORED. To avoid a spontaneous combustion fire, immediately after each use place rags, steel wool, brushes, rollers or waste in a sealed, water-filled metal container. Keep away from combustible materials. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency. Harmful or fatal if swallowed. Keep away from open flame or spark. Use only with adequate ventilation

FIRST AID TREATMENT:

Refer to the Material Safety Data Sheet.

The technical information and suggestions for use made herein are based on Akzo Nobel Coatings Inc.'s research and experience and are believed to be reliable, but such information and suggestions do not constitute a warranty.

Since Akzo Nobel Coatings Inc. has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves, by preliminary tests or otherwise, the suitability of the product for their purposes. When testing, the complete system that has been chosen must be applied.

PROPERTIES**COLOR RANGE****PACKAGING****STORAGE****HEALTH & SAFETY DATA****PRODUCT DISCLAIMER**