



Perma-Chink Systems **Ultra Deck Oil** is a specially formulated blend of resins and oil to provide a superior natural finish for decks, siding, shingles, shakes and trim. **Ultra Deck Oil** comes in the same transparent tones as LIFELINE Ultra-1 Stain & Finish. Because **Ultra Deck Oil** is a penetrating oil formula, you should expect color development to be slightly different between these two high quality transparent wood finishes. **Ultra Deck Oil** is a penetrating oil finish containing UV inhibitors and transparent pigments for excellent protection against UV radiation and other damaging weather elements. It forms a penetrating water repellent layer at the wood surface to protect against checking and warping. The stain contains mildew preventatives to resist mildew growth on the surface of the finish. **Ultra Deck Oil** is an easy-to-apply one coat penetrating finish. **Ultra Deck Oil** slowly weathers away with time to natural wood hues, depending on the color chosen, the wood species and the amount of time involved.

#### **DIRECTIONS FOR USE ULTA DECK OIL**

Note to user: Read all label instructions carefully. Finished appearance will vary depending on porosity and color of wood surface, preparation methods and application techniques. To ensure desired appearance, always apply to a small test area and allow to dry before proceeding.

#### **Step # 1: Inspection**

Check for deterioration and decay. Repair decomposed wood by appropriate means. Contact Perma-Chink Systems, Inc. for information about restoration methods.

#### **Step # 2: Surface Preparation**

Proper preparation is the key to maximum performance & best appearance. Surface should be free from mill glaze, contaminants (e.g. dirt, dust, rust stains, water repellents, mildew and other foreign materials) and loose wood fiber. For Ultra Deck Oil to properly penetrate, surface must be structurally sound, free from any sealants and absolutely dry. (Moisture content below 15% or exposed to dry weather a minimum of 5 days.) If surface sealants are present, they must be completely removed. Weathered wood surfaces should be properly prepared using Wood ReNew, Oxcon or other preparation methods. New smooth wood that is unseasoned may require removal of mill glaze and adequate drying time before application of Ultra Deck Oil. Avoid the use of chlorine or other highly caustic cleaners unless absolutely necessary. Remove all residues from cleaners used on wood surfaces.

### **Step # 3: Application**

Stir thoroughly before and frequently during use to make sure that colorants are evenly dispersed. When using more than one container, blend the containers together. Do not thin. Apply one coat only, evenly with brush or spray. When spraying, always backbrush immediately after each section is coated to ensure proper penetration and even coverage. On decks or any horizontal surface, it is important to apply only one coat and only with a brush. Best results are obtained using a high-quality natural bristle brush. Apply to small sections at a time. Avoid lap marks by starting at one edge and following through to the end of boards – keep a wet edge. Apply when surfaces are protected from direct sunlight. Surface temperature should be between 50°F and 90°F. Do not apply when rain is expected within 24 hours. Ultra Deck Oil dries in approximately 24 hours, at 70°F and 50% relative humidity.

### **Step # 4: Clean-Up**

Clean brushes and equipment with mineral spirits. Dispose of empty cans or unused portion in accordance with local, state and federal regulations. Close container when not in use. Rags, steel wool, or waste soaked with Ultra Deck Oil may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in a sealed, water-filled metal container.

### **Step # 5: Coverage**

On smooth surfaces, approximately 400-500 square feet per gallon. On rough surfaces, 150-250 square feet per gallon. Rates also vary according to porosity of wood surface.

### **Step # 6: Maintenance**

Apply periodic maintenance coats as necessary. We suggest that you apply the first maintenance coat approximately 1 year after the first application. Thereafter, determine the need for maintenance coats by inspection of appearance and water repellent qualities. (Usually 1-2 year periods for decks, 2-4 years for vertical surfaces).

### **Step # 7: Storage**

Store Ultra Deck Oil out of direct sunlight. Keep unused material in tightly closed container. Ultra Deck Oil should be good for 5 years when stored in original factory sealed container. During long-term storage, settling of some ingredients may occur. Mix or shake thoroughly.

### **CAUTION**

Combustible. Contains Petroleum Distillates. Keep away from heat and flame. May be harmful if inhaled or swallowed. May be irritating to eyes and skin. Not intended for interior surfaces. For exterior use only. Avoid breathing vapors – use only in areas of adequate ventilation. Wear a vapor/mist respirator during spray applications. If you experience eye watering, headaches or dizziness, increase

fresh air or wear respiratory protection (NIOSH/MSHA TC 23 C or equivalent) or leave the area. Keep container closed when not in use.

#### **DANGER**

**Rags, steel wool or waste soaked with Ultra Deck Oil may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in sealed, water-filled metal container.**

#### **FIRST AID**

**IF SWALLOWED, DO NOT INDUCE VOMITING, CALL PHYSICIAN**

**IMMEDIATELY. EYES:** Flush eyes immediately with water for 15 minutes. Call physician. **SKIN:** Wash thoroughly with soap and water. Remove contaminated clothing. Call physician if irritation persists.

#### **NOTICE**

Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **WARNING:** This product contains a chemical known to the state of California to cause cancer.

#### **KEEP OUT OF REACH OF CHILDREN**

#### **LIMITED WARRANTY**

When applied to new wood according to the directions on the label, if this Ultra Deck Oil is proved to be defective after purchase, Perma-Chink Systems, Inc., will furnish any necessary additional product fee of charge or will refund the purchase price at the company's option. This warranty does not include labor or cost of labor for the application of the product. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. This product contains a maximum of 350 grams/liter (2.9 lbs./gal.) of Volatile Organic Compound (VOC).

#### **CONTAINS:**

Petroleum Distillate (8052-41-3), Alkyd Resin (66070-60-8), Linseed Oil (8001-26-1), Mildewicide (133-07-03), Organoclay (proprietary).



[www.permachink.com](http://www.permachink.com)